WSOLAR
solar power solutions

WS-M250~265

MONO-CRYSTALLINE MODULES




Features

- **10**years, **12**years, **30**years lifetime Warranty.
- Positive tolerance **0~+3%** ensures power output.
- Performance double warranted by **Zurich** Insurance.
- **CPK>1.33**, ensured module quality.
- Module can bear snow loads up to **5400Pa** and wind loads up to **3800Pa**.







WSOLAR is a high tech company focusing on production of solar cells and modules.We strictly carry on quality control system ISO9001 and every module is with the qualifications of CE, TUV, UL, IEC61215, IEC61730, PV CYCLE and MCS etc... Most of our modules are applied in residential, commercial and industrial projects by on-grid and off-grid systems throughout the world, bringing clean and sustainable energy for everyone.

WS-M250~265

Specifications

Model type	WS-M250	WS-M255	WS-M260	WS-M265
Peak power - Pmax (W)	250	255	260	265
Open circuit voltage - Voc (V)	59.8	59.8	60.1	60.4
Maximum power voltage - Vmp (V)	49.0	49.0	49.1	49.6
Short circuit current - Isc (A)	5.51	5.62	5.72	5.80
Maximum power current - Imp (A)	5.10	5.20	5.30	5.35
Cell efficiency μc (%)	17.33	17.68	18.03	18.38
Module efficiency μm (%)	14.86	15.15	15.45	15.75
Maximum system voltage	1000V DC			
Maximum series fuse rating	10A			
Power tolerance	0~+3%			
Temperature coefficients of Pmax	-(0.5±0.05)%/℃			
Temperature coefficients of Voc	-(160±10)mV/℃			
Temperature coefficients of Isc	(0.065±0.015)%/℃			
Nominal operating cell temperature	47±2℃			

Standard testing condition (STC): Irradiance 1000W/m², Temperature: 25℃, AM=1.5

Qualification test parameters

Operating temperature	-40 ℃ to +85 ℃
Storage temperature	-40 ℃ to +85 ℃
Pressure bearing	≥5400 Pascal
Wind bearing	≥3800 Pascal

Packing configuration


Container	20'GP	40'GP	40'HQ
Pieces per pallet	19	19	21
Pallets per container	12	28	28
Pieces per container	228	532	588

Mechanical characteristics

Cell size	Mono 125*125 (5inch)
No. of cells	96pcs (8*12)
Dimension	1580*1065*50mm
Weight	21.5kg
Glass	3.2mm high transmission, low iron, tempered glass
Frame	Anodized aluminum alloy
Junction box	MC4 connector, TUV certified
Internal diodes	3 bypass diodes
Cable	Section: 4.0mm² Length: 900mm


Product dimension

Unit: mm



Electrical performance

Cell temperature 25℃



CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
© April 2012 WSOLAR Limited. ALL rights reserved. Specifications included in this datasheet are subject to change without notice.